

2) **Servicing Personnel:** Do not attempt to service the unit beyond that described in these operating instructions. Refer all other servicing to authorized servicing personnel.

3) **Replacement parts:** When parts need replacing ensure the servicer uses parts specified by the manufacturer or parts that have the same characteristics as the original parts. Unauthorized substitutes may result in fire, electric shock, or other hazards.

4) **Safety check:** After repairs or service, ask the servicer to perform safety checks to confirm that the unit is in proper working condition.

### WARRANTY

If your product does not work properly because of a defect in materials or workmanship, our Company (referred to as "the warrantor" ) will, for the length of the period indicated as below, **(Parts(1) Year, Labor(90) Days)** which starts with the date of original purchase ("Limited Warranty period"), at its option either (a) repair your product with new or refurbished parts, or (b) replace it with a new or a refurbished product. The decision to repair or replace will be made by the warrantor.

During the "Labor" Limited Warranty period there will be no charge for labor. During the "Parts" warranty period, there will be no charge for parts. You must mail-in your product during the warranty period. This Limited Warranty is extended only to the original purchaser and only covers product purchased as new. A purchase receipt or other proof of original purchase date is required for Limited Warranty service.

### MAIL-IN SERVICE

When shipping the unit carefully pack and send it prepaid, adequately insured and preferably in the original carton. Include a letter detailing the complaint and provide a day time phone and/or email address where you can be reached.

### LIMITED WARRANTY LIMITS AND EXCLUSIONS

1) This Limited Warranty ONLY COVERS failures due to defects in materials or workmanship, and DOES NOT COVER normal wear and tear or cosmetic damage.

The Limited Warranty ALSO DOES NOT COVER damages which occurred in shipment,

or failures which are caused by products not supplied by warrantor, or failures which result from accidents, misuse, abuse, neglect, mishandling, misapplication, alteration, faulty installation, set-up adjustments, misadjustment of consumer controls, improper maintenance, power line

surge, lightning damage, modification, or service by anyone other than a Factory Service center or other Authorized Servicer, or damage that is attributable to acts of God.


2) THERE ARE NO EXPRESS WARRANTIES EXCEPT AS LISTED UNDER "LIMITED WARRANTY COVERAGE". THE WARRANTOR IS NOT LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OF THIS PRODUCT, OR ARISING OUT OF ANY BREACH OF THIS WARRANTY. (As examples, this excludes damages for lost time, cost of having someone remove or re-install an installed unit if applicable, travel to and from the service, loss of or damage to media or images, data or other recorded content. The items listed are not exclusive, but are for illustration only.)

3) PARTS AND SERVICE, WHICH ARE NOT COVERED BY THIS LIMITED WARRANTY, ARE YOUR RESPONSIBILITY.

## HDMI Extender

MODEL:LM-EX11

### Operating Instructions



### Dear Customer

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference.

## FEATURES

- Each set includes one transmitter and one receiver.
- Use **single** UTP LAN cable (Cat5E/6) to substitute HDMI cable to achieve long distance transmission, the UTP Cable follows the standard of IEEE-568B.
- Transmission distance extend up to 50 meters under 1080P .
- Supports Deep Color up to 36 bits.
- Supports lossless compressed digital audio: Dolby TrueHD, DTS-HD Master Audio.
- Transmit Digital Audio and Video over the CAT6 / CAT5e cable with zero signal loss.
- Data transfer speed 6.75 Gbps.
- DC 5V power supply.

## NOTICE

Our company reserve the right to make changes in the hardware, packaging and any accompanying documentation without prior written notice.

1

Operating Instructions

## TABLE OF CONTENTS

Specifications  
 Package Contents  
 Panel Descriptions  
 Connecting and Operating  
 Maintenance  
 Product Service  
 Warranty

## SPECIFICATIONS

Operating	-5 to +35℃ (+23 to +95°F)
Operating Humidity	5 to 90%RH (No Condensation)
Input Video Signal	0.5-1.0 Volts P-P
Input DDC Signal	5 volts p-p(TTL)
Support Video Format	DTV/HDTV:480i/576i/480P/576P/720P/1080i/1080P
Video Output	HDMI , HDCP1.1
Support Audio Format	DTS-HD Master Audio、Dolby true-HD etc.
Transmission	1080P 8-bit 50m(Maximum) over single
Power consumption	5watts(Maximum)

Dimension (L×W×H)	83x48x25mm
Net Weight	250g(Pair)

Note1: Specifications are subject to change without notice. Mass and dimensions are approximate.


①Sink must support 3D video when sources is 3D device

②: When in 36Bits deepcolor mode, we suggest set the HDMI source device to output 1080i or 720p.


## PACKING CONTENTS

- 1) Main Unit. Transmitter & Receiver HDMI Extender
- 2) DC 5V 1A x2PCS
- 3) Operating Instructions

## PANEL DESCRIPTIONS



Operating Instructions



1. Status of signal connection
2. HDMI input
3. Status of power input
4. CAT-5E/6 output
5. Power input
6. HDMI output
7. CAT-5E/6 input

## CONNECTING AND OPERATING

- 1) Connect the HDMI signal sources (Such as PS3, STB etc) to HDMI Transmitter.
- 2) Connect CAT5e or 6cables to both the outputs of the transmitter and inputs of the Receiver. (The cables must follow the standard of EIA-TIA 568B).
- 3) Connect the HDMI output (Such as HD-LCD, HD-DLP) into the Receiver.  
Attention: Insert/Extract cables gently.

## **MAINTENANCE**

Clean this unit with a soft, dry cloth. Never use alcohol, paint thinner or benzine to clean this unit.

## **PRODUCT SERVICE**

### **1) Damage requiring service:**

The unit should be serviced by qualified service personnel if:

- (a) The DC power supply cord or AC adaptor has been damaged;
- (b) Objects or liquids have gotten into the unit;
- (c) The unit has been exposed to rain;
- (d) The unit does not operate normally or exhibits a marked change in performance;
- (e) The unit has been dropped or the cabinet damaged.